

Product information AVOL STREICHERT f_12108



Description:

Fully synthetic premium automatic transmission oil has been specially developed for all 6-, 8- and 9-speed ZF transmissions. Provides high thermal stability, ensuring ideal ageing resistance. Secures maximum transmission performance. Guarantees maximum performance even with the longest oil-change intervals.

Approvals and specifications:

BMW ATF 3+
BMW 83 22 2 305 397
BMW 83 22 2 152 426
BMW 83 22 2 289 720
Chrysler 68157995AA, 68157995AB
Chrysler 68218925AA, 68218925GA
Fiat 9.55550-AV5
Honda ATF-Type 3.1
Honda 08263-999-01HE, 08200-9017
Jaguar 02JDE 26444
Land Rover LR023288, LR023289
VW G 055 162
VW G 060 162 A1/A2/A6
ZF S671 090 312
ZF AA01.500.001



Technical data:

Density at 20°C	0.841 g/ml EN ISO 3675
Viscosity at 40°C	29.7 mm ² /s EN ISO 3104
Viscosity at 100°C	6.0 mm ² /s EN ISO 3104
Viscosity index	153 ISO 2909
Pour point	-45°C ISO 3016
Flash point	210°C EN ISO 2592
Viscosity at -40°C (Brookfield)	<= 10000 mPas ASTM D 2983

Our information is based on thorough research and may be considered reliable, although not legally binding.