

Product information

AVOL STREICHERT f_71141



Description:

Fully synthetic automatic transmission oil of the latest generation. For automatic transmissions, manual shift transmission, steering systems, hydraulic and lateral drives both in the car and in the commercial vehicle sector. Ensures exact friction behavior and guarantees outstanding ageing resistance. Secures the functional performance of the aggregate and ensures long service life.

Approvals and specifications:

Aisin Warner JWS 3309/3314/3317
BMW LT 71141, 7045 E, 8072 B, LA 2634
BMW 8322 9407807
Fiat 9.55550-AV4
Ford Mercon V
GM Dexron III H
Honda ATF Z1 (ausser CVT)
Hyundai SP-II, SP-III
Mazda ATF M-III, M-V
MB 236.11, 236.10, 236.9, 236.7
MB A 001 989 22 03
Mitsubishi SP-II, SP-III
Nissan Matic D, J, K



Porsche 999.917.547.00
Subaru ATF
Toyota Type T-IV, T-III
Volvo 97340, 97341
VW G 055 025 (A2), G 052 055
VW G 052 162 (A1, A2, A6), G 052 990 (A2)
ZF TE-ML 02F/03D/04D/05L/09
ZF TE-ML 11A/11B/14A/14B/17C
ZF S671 090 170
Allison C4, TES 295
Caterpillar TO-2
MAN 339 V1, 339 Z1, 339 Z2
Voith G607 (55.6335)

Technical data:

Density at 20°C	0.842 g/ml EN ISO 3675
Viscosity at 40°C	35.1 mm ² /s EN ISO 3104
Viscosity at 100°C	6.9 mm ² /s EN ISO 3104
Viscosity index	161 ISO 2909
Pour point	-49°C ISO 3016
Flash point	228°C EN ISO 2592
Viscosity at -40°C (Brookfield)	<= 20000 mPas ASTM D 2983

Our information is based on thorough research and may be considered reliable, although not legally binding.