

Product information

AVOL STREICHERT f_G45 75W-90



Description:

Fully synthetic TDL ("total drive line") hypoid gear oil with extremely high performance reserves. Even under the most difficult conditions and during large temperature fluctuations, it ensures flawless aggregate functioning. Enables long oil change intervals.

Approvals and specifications:

API GL 4/5, API MT-1
BMW 83 22 2 365 987
Ford M2C-175A
Opel B 040 1031
VW G 052 145, G 052 911
ARVIN MERITOR 0-76-N
DAF GL5/MIL-PRF-2105E
IVECO MIL-PRF-2105E
MACK GO-J
MAN 341 Z-2, 342 M-3, 341 E-3, 3343SL
MB 235.8
MIL PRF-2105E
RENAULT B0032/3 Annex 3
SAE J 2360
SCANIA STO 1:0
Volvo 97310
ZF TE-ML 02B, 05B, 07A, 08, 12B, 12L, 12N, 16F, 17B, 19C, 21B



Technical data:

SAE class (transmission oils)	75W-90 SAE J306
Density at 20°C	0.860 g/ml EN ISO 3675
Viscosity at 40°C	92.0 mm ² /s EN ISO 3104
Viscosity at 100°C	16.1 mm ² /s EN ISO 3104
Viscosity index	189 ISO 2909
Pour point	-49°C ISO 3016
Flash point	184°C EN ISO 2592
Viscosity at -40°C (Brookfield)	110000 mPas ASTM D 2983

Our information is based on thorough research and may be considered reliable, although not legally binding.