

## Product information

### AVOL STREICHERT f\_MSP/A 75W-140 LS



#### Description:

Fully synthetic hypoid transmission oil with extremely high performance reserves. For highly stressed axle drives with and without limited-slip differentials – especially for vehicles in which the aggregate or vehicle manufacturer specifies oil with Limited Slip additives (LS). Ensures exact friction behavior and provides outstanding ageing resistance. Even under the most difficult conditions and during large temperature fluctuations, it ensures flawless aggregate functioning.

#### Approvals and specifications:

API GL-5  
BMW MSP/A  
MB 235.61  
Ford WSL-M2C 192A  
ZF TE-ML 05D/12D/16G/21D  
Scania STO 1:0  
MIL-L-2105 C/D



#### Technical data:

SAE class (transmission oils)	75W-140 SAE J306
Density at 20°C	0.870 g/ml EN ISO 3675
Viscosity at 40°C	179.0 mm²/s EN ISO 3104
Viscosity at 100°C	26.5 mm²/s EN ISO 3104
Viscosity index	184 ISO 2909
Pour point	-51°C ISO 3016
Flash point	200°C EN ISO 2592
Viscosity at -40°C (Brookfield)	130000 mPas ASTM D 2983

Our information is based on thorough research and may be considered reliable, although not legally binding.