

## Product information

### AVOL STREICHERT FRACHT\_G92 15W-40



#### Description:

AVOL FRACHT\_G92 15W-40 is designed to meet the requirements of today's modern four-stroke engines, formulated to provide reliable protection for trucks and buses which run on compressed natural gas (CNG), liquefied natural gas (LNG) or liquefied petroleum gas (LPG). AVOL FRACHT\_G92 15W-40 uses high-quality base oils and an advanced additive system with low-sulphated ash which delivers exceptional thermal and oxidative stability as well as nitration resistance.

**Specifications and approvals //or// AVOL STREICHERT recommends this product for vehicles with the following specifications:**

API CK-4, CJ-4, CI-4  
API SN  
Cummins CES 20092  
Cummins CES 20086, 20085  
Detroit Diesel 93K222  
Renault RLD-4  
Mack EOS-4.5  
Volvo VDS-4.5



#### Technical data:

SAE class (engine oils)	15W-40 SAE J300
Density at 20°C	0.875 g/ml EN ISO 3675
Viscosity at 40°C	111.5 mm <sup>2</sup> /s EN ISO 3104
Viscosity at 100°C	14.9 mm <sup>2</sup> /s EN ISO 3104
Viscosity index	138 ISO 2909
Pour point	-38°C ISO 3016
Flash point	233°C EN ISO 2592
Total base number	9.9 mg KOH/g ASTM D 2896
Sulfate ash	0.8 g/100g EN ISO 3987

Our information is based on thorough research and may be considered reliable, although not legally binding.