

Product information AVOL STREICHERT kfs_F



Description:

Radiator antifreeze based on ethylene glycol. Provides outstanding protection against frost, corrosion and overheating and does not contain amines, nitrites, phosphates, borates or silicates. With an ingenious OAT inhibitor package specially developed for modern aluminum high-performance engines.

Specifications and approvals //or// AVOL STREICHERT recommends this product for vehicles with the following specifications:

Fiat 9.55523	Cummins CES 14439
Ford WSS-M97 B44-D	Cummins CES 14603
GMW 3420	DAF 74002
Jaguar CMR 8229	Detroit DFS93K217
Mazda MEZ MN 121 D	Deutz DQC CB-14
MB 325.3, MB 326.3	Jenbacher TA 1000-2000
Renault 41-01-001/--S Type D	John Deere JDM H5
Saab B040 1065	Komatsu 07.892 (2009)
Skoda 61-0-0257	Leyland Trucks DW03245403
STJLR.651.5003	Liebherr MD1-36-130
VW TL-774 F (G12+), TL-774 D (G12)	Mack 014 GS 17009
Bergen Engines 2.13.01	MAN 324 Typ SNF
Case New Holland MAT 3624	MTU MTL 5048
Caterpillar GCM34	Wärtsila 32-9011



Mixing table:

Frost protection till	AVOL kfs_F (Part)	Water (Part)
-17°C	1	2
-25°C	1	1.5
-40°C	1	1
-55°C	1.5	1
-70°C	2	1

Technical data:

Water content	<= 4%
Base	Ethylene glycol with inhibitors
Color / appearance	Pink-red, fluorescent
Boiling point	177°C ASTM D 1120
pH value	8.5 ASTM D 1287
Density at 20°C	1.12 g/cm ³ ASTM D 1122

Our information is based on thorough research and may be considered reliable, although not legally binding.