

Product information
AVOL STREICHERT s_ECOGRÜN 0W-20



Description:

Fully synthetic low-viscosity premium class motor oil with outstanding wear-protection formula for modern hybrid and petrol engines. Fastest cold-start oiling during starting and minimum friction during daily driving ensure an extremely long engine service life.

Specifications and approvals //or// AVOL STREICHERT recommends this product for vehicles with the following specifications:

ACEA C5, C6
API SQ, SP (RC)
ILSAC GF-7A
BMW Longlife-14 FE+
BMW Longlife-17 FE+
Chrysler MS-12145
Chrysler MS-13340
Chrysler MS-6395
Fiat 9.55535-CR1
Ford WSS-M2C947-A/B1
Ford WSS-M2C962-A1
GM dexos1 Gen 3
Honda/Acura HTO-06
MB 229.72, MB 229.71
Porsche C20
Volvo VCC RBS0-2AE
VW 508.00/509.00



Technical data:

SAE class (engine oils)	0W-20 SAE J300
Density at 20°C	0.846 g/ml EN ISO 3675
Viscosity at 40°C	45.8 mm ² /s EN ISO 3104
Viscosity at 100°C	8.7 mm ² /s EN ISO 3104
Viscosity index	172 ISO 2909
Pour point	-43°C ISO 3016
Flash point	228°C EN ISO 2592
Total base number	8.0 mg KOH/g ASTM D 2896
Sulfate ash	0.8 g/100g EN ISO 3987

Our information is based on thorough research and may be considered reliable, although not legally binding.